

[illegible]

Technical drawing of a rectangular plate. The top view shows a rectangle with overall dimensions 670 (width) and 164 (height). The width is divided into segments of 42, 2, 616 ±3, and 10. The height is divided into segments of 24, 130, and 10. The side view shows a rectangle with overall dimensions 630 (width) and 40 (height). The width is divided into segments of 45, 2, 623 ±3, and 10. The height is divided into segments of 24, 130, and 10. The drawing includes dimension lines, arrows, and tolerance symbols (±3).

Technical drawing of a U-shaped profile. The drawing shows the profile with dimensions and tolerances. The overall width is 920, with a central width of 780 ± 4 and side flanges of 70. The overall height is 670, with an inner height of 600 ± 3 and a bottom flange of 70. The bottom flange has a width of 800 ± 4 and side flanges of 60. The inner corner radius is specified as max. R25 ± 5 and the outer corner radius as max. R5 ± 5 . The drawing is oriented with the U-shape opening to the right. Section lines 1-1 and 2-2 are indicated.

Rubrik: H2001	Art.-Nr: 132316	HW: 11	Massstab: 1:25	Format: DIN A3
Lichtschacht			Gezeichnet: 19.07.2024/JCD	Geprüft: 19.07.2024/ange/hawü
Lichtschacht bewehrt LW 80 x 60 cm			Änderung:	Geprüft:
			Änderung:	Geprüft:
			Änderung:	Geprüft:
L 800 mm, S 600 mm, H 140 mm, W 60 mm			Ersetzt:	
 CREABETON BAUSTOFF AG 6221 Rickenbach LU info@creabeton-baustoff.ch Telefon 0848 400 401 CREABETON MATERIAUX AG 3250 Lyss BE			Plan-Nr: H2001_132316_11_PZ_01_01	
Diese Zeichnung ist geistiges Eigentum des HW und darf ohne deren Einwilligung weder kopiert, vervielfältigt, weitergegeben, noch zur Ausführung benutzt werden. Art. 5 des Bundesgesetzes gegen den unlauteren Wettbewerb (UWG).				